


# CR1620

## CR Coin-type Lithium Battery




### Features & Benefits

- Offers high-rate pulse discharge
- Available in a range of compact sizes and capacities, from thin-type to high-capacity models
- Excellent low-temperature performance enhanced by manganese-dioxide positive pole


### Applications

Remote keyless entry, Card remote controls, memory backup, security price tags, smart transmitter tags and others.

#### Discharge temperature characteristics



#### Capacity vs. load resistance



### Specifications

<b>Nominal voltage</b>		3V
<b>Nominal capacity</b>		75mAh
<b>Continuous drain</b>		0.1mA
<b>Dimensions*<sup>1</sup></b>	<b>Diameter(Max.)</b>	16.0mm
	<b>Height(Max.)</b>	2.0mm
<b>Weight*<sup>1</sup></b>		Approx. 1.3g
<b>Operating temperature*<sup>2</sup></b>		-30°C to +85°C

\*<sup>1</sup> Without tabs.

\*<sup>2</sup> Please consult Panasonic when anticipating usage in operating temperatures of 70°C or above.

### Terminal types

Please see the documents for the terminal and lead wire settings.

- [Line up of tab terminal types\(by shape\)](#)
- [Line up of tab terminal types\(by product number\)](#)

#### Operating voltage vs. load resistance (voltage at 50% discharge depth)

